



TOYO TIRES®



TOYO PROXES RS1

| Tire Size | Load ID | Product Code | Approved Rim Width Range (inch) | Tread Depth (1/32") | Overall Diameter (inch) | Overall Width (inch) | Static Loaded Radius (inch) | Revs Per Mile |
|------------|---------|--------------|---------------------------------|---------------------|-------------------------|----------------------|-----------------------------|---------------|
| 245/640R18 | SL | 163460 | 8.5 | 0 | 25.4 | 9.8 | 11.9 | 818 |
| 285/650R18 | SL | 171680 | 10 | 0 | 25.5 | 11.1 | 11.9 | 814 |
| 285/680R18 | SL | 163450 | 10 | 0 | 26.7 | 11.7 | 12.4 | 778 |
| 335/710R18 | SL | 171440 | 12 | 0 | 27.7 | 13.4 | 12.8 | 749 |

Bold designates measuring rim width
 RD = Reinforced
 XL = Extra load
 LL = Light Load

- Advanced casing provides durability at high speed
- Stiff construction provides crisp and responsive handling
- Durable, race-proven compound is excellent in dry braking
- Steel wire reinforced sidewall creates linear response and better handling
- Spiral wound cap ply provides uniformity and consistency

Toyo Tires recommends the following general set up guidelines for the Proxes RS1:

Operating Temperature: 160°F to 220°F
 Hot Inflation Pressures: High 30s to Low 40s (psi)
 Camber: -2.5° to -5.0°
 Caster: As much positive as possible