

NOTES

Lined area for notes, consisting of multiple horizontal dashed lines on a white background.

MICHELIN CIRCUIT RANGE
TOURING / GT



MICHELIN CIRCUIT RANGE TOURING / GT

CIRCUIT DIMENSIONS TOURING / GT

SLICK TYRES

Available in 15", 17", 18" et 19"

Tyres exclusively intended for circuit use in dry conditions. Up to three different treads are available on certain sizes, enabling their use in disciplines from Sprint races to Endurance races.



27/65-18 S9L

RAIN TYRES

Available in 15", 17", 18" et 19"

Each slick tyre comes with its grooved equivalent, to ensure good traction in wet conditions.



31/71-18 P2L

DIMENSIONS	RAIN	SLICK		
		SOFT	MEDIUM	HARD
18/58 - 15	P2L			S9L
19/57 - 15	P2G		S8B	S9C
33/70 - 15	P2G			S9D
23/61 - 16	P2L			S9L
20/61 - 17	P2G		S8L	S9D
24/61 - 17	P2E		S8C / S8L	
24/64 - 17	P2G	S8D* / S8M		
21/65 - 18	P2G*		S8C*	
24/64 - 18	P2G*	S7A*		S9F
24/65 - 18	P2G		S8C	
24/65 - 19	P2G		S8A	
25/64 - 18	P2L		S8L	S8A / S9L
27/65 - 18	P2G/ P2L		S8L	S9L
28/69 - 19	P2G			S9A
29/67 - 19			S8A	S9A
30/65 - 18	P2L	S7L	S8L / S8M**	S9L / S9M**
30/68 - 18	P2L	S7L	S8L	S9L / S9M**
31/71 - 18	P2L	S7L	S8L	S9L / S9M**
31/71 - 19	P2L	S7L	S8L	S9L / S9M**

* Limited stocks available. / ** Available in 2017.

CIRCUIT TECHNICAL DATA

TOURING / GT

DESIGNATION	TYPE	RECOMMENDED RIM (")	TREAD WIDTH (MM)	TYRE WIDTH (MM)	INFLATED DIAMETER (MM)	TREAD CIRCUMFERENCE (MM)
18/58-15	S9L	8	178	220	583	1832
18/58-15	P2L	8	179	220	588	1847
19/57-15	S8B	7	185	212	568	1744
19/57-15	S9C	7	185	212	568	1744
19/57-15	P2G	7	185	210	571	1753
33/70-15	S9D	14	310	390	694	2142
33/70-15	P2G	14	310	390	694	2137
23/61-16	S9L	10	236	276	616	1935
23/61-16	P2L	10	236	276	620	1947
20/61-17	S8L	8	190	225	604	1890
20/61-17	S9D	8	187	219	606	1870
20/61-17	P2G	8	191	223	604	1854
24/61-17	S8C	9	235	250	605	1857
24/61-17	S8L	9	235	248	605	1857
24/61-17	P2E	9	224	246	605	1857
24/64-17	S8D*	9	230	254	640	1965
24/64-17	S8M	9	226	254	639	2007
24/64-17	P2G	9	226	254	639	2007

* Limited stocks available.



CIRCUIT TECHNICAL DATA

TOURING / GT

DESIGNATION	TYPE	RECOMMENDED RIM (")	TREAD WIDTH (MM)	TYRE WIDTH (MM)	INFLATED DIAMETER (MM)	TREAD CIRCUMFERENCE (MM)
21/65-18	S8C*	8	196	225	651	2006
21/65-18	P2G*	8	196	225	651	2006
24/64-18	S7A*	9,5	230	254	639	1962
24/64-18	S9F	9,5	230	254	639	1962
24/64-18	P2G*	9	240	252	640	1965
24/65-18	S8C	9	229	251	647	1988
24/65-18	P2G	9	226	255	650	2007
25/64-18	S8A	10	237	267	643	1975
25/64-18	P2L	10	231	269	647	2031
25/64-18	S8L	10	249	271	642	1990
25/64-18	S9L	10	249	271	642	1990
27/65-18	S8L	11	260	298	648	1990
27/65-18	S9L	11	260	298	648	1990
27/65-18	P2G	11	260	295	652	2002
27/65-18	P2L	11	260	299	652	2048
30/65-18	S7L	12,5	288	329	650	1996

* Limited stocks available.



