



**TOYO TIRES®**

6.3/32" tread depth 100 UTQG



Toyo Tires recommends the following general setup guidelines for the Proxes R888R:

Operating Temperature: 160°F to 220°F

Hot Inflation Pressures: 32 to 38 (psi)

Camber: -1° to -3°

Caster: As much positive as possible

*TOYO PROXES R888R*

Tire Size	Load ID	Product Code	Rim Width Range	Weight (lbs)	Overall Diameter	Overall Width	Max Load (lbs)	Max PSI	Revs Per Mile
185/60R13 80V	SL	103180	5.0- <b>5.5</b> -6.5	17	21.7"	7.4	992	51	956
205/60R13 86V	SL	103200	5.5- <b>6.0</b> -7.5	20	22.7"	8.2	1168	51	916
225/45R13 84V	SL	104530	7.0-7.5-8.5	19	20.9	8.9	1102	51	992
185/60R14 82V	SL	103190	5.0- <b>5.5</b> -6.5	18	22.8"	7.4	1047	51	913
195/50R15 82V	SL	102740	5.5- <b>6.0</b> -7.0	19	22.7"	7.9	1047	51	914
195/55R15 85V	SL	103520	5.5- <b>6.0</b> -7.0	20	23.4"	7.9	1135	51	887
205/50ZR15 86W	SL	103210	5.5- <b>6.5</b> -7.5	20	23.1"	8.4	1168	51	899
225/45ZR15 87W	SL	104470	7.0-7.5-8.5	21	23	8.9	1201	51	905
225/50ZR15 91W	SL	103510	6.0- <b>7.0</b> -8.0	23	23.9"	9.2	1356	51	869
235/50ZR15 94W	SL	104320	6.5- <b>7.5</b> -8.5	23	24.3"	9.6	1477	51	855
195/50ZR16 84W	SL	103500	5.5- <b>6.0</b> -7.0	20	23.7"	7.9	1102	51	876
205/45ZR16 83W	SL	103800	6.5- <b>7.0</b> -7.5	21	23.2"	8.1	1074	51	894

205/50ZR16 87W	SL	103810	5.5- <b>6.5</b> -7.5	22	24.1"	8.4	1201	51	862
205/55ZR16 94W	XL	104310	5.5- <b>6.5</b> -7.5	23	24.9"	8.4	1477	51	835
225/45ZR16 89W	SL	103530	7.0- <b>7.5</b> -8.5	23	23.9"	8.9	1279	51	868
245/45ZR16 94W	SL	104330	7.5- <b>8.0</b> -9.0	24	24.6"	9.6	1477	51	843
255/50ZR16 99W	SL	104480	7.0- <b>8.0</b> -9.0	28	26.1	10.4	1709	51	797
205/40ZR17 80W	SL	103540	7.0- <b>7.5</b> -8.0	20	23.5"	8.3	99	51	885
205/45ZR17 84W	SL	103850	6.5- <b>7.0</b> -7.5	22	24.3"	8.1	1102	51	857
205/50ZR17 89W	SL	103820	5.5- <b>6.5</b> -7.5	23	25.1"	8.4	1279	51	827
215/45ZR17 87W	SL	103390	<b>7.0</b> -8.0	22	24.6"	8.4	1201	51	843
225/45ZR17 94W	SL	106910	7.0- <b>7.5</b> -8.5	24	25.0"	8.9	1356	51	832
235/40ZR17 90W	SL	103410	8.0- <b>8.5</b> -9.5	24	24.4"	9.5	1323	51	851
235/45ZR17 94W	SL	103860	7.5- <b>8.0</b> -9.0	25	25.4"	9.3	1477	51	819
245/40ZR17 91W	SL	104510	8.0-8.5-9.5	24	24.7	9.8	1356	51	840
255/40ZR17 94W	SL	103880	8.5- <b>9.0</b> -10.0	26	25.0"	10.2	1477	51	830
275/40ZR17 98W	SL	104520	9.0-9.5-11.0	28	25.7	10.9			
315/35ZR17 102W	SL	104430	10.5- <b>11.0</b> -12.5	31	25.7"	12.6	1874	51	809
225/40ZR18 92Y	XL	102700	7.5- <b>8.0</b> -9.0	24	25.1"	9.1	1389	50	828
235/40ZR18 91Y	SL	103420	8.0- <b>8.5</b> -9.5	25	25.4"	9.5	1356	51	818
245/40ZR18 93Y	SL	103870	8.0- <b>8.5</b> -9.5	26	25.7"	9.8	1433	51	808
255/35ZR18 90Y	SL	103830	8.5- <b>9.0</b> -10.0	26	25.0"	10.2	1323	51	831
265/35ZR18 97Y	SL	104570	9.0- <b>9.5</b> -10.5	28	25.3"	10.7	1433	51	821
275/35ZR18 95Y	SL	104260	9.0- <b>9.5</b> -11.0	28	25.6"	10.9	1521	51	813
295/30ZR18 98Y	XL	104270	10.0- <b>10.5</b> -11.0	29	25.0"	11.9	1653	50	831
305/35ZR18 105Y	RD	104460	10.0-11.0-12.0	32	26.4"	12.3	2039	50	786
315/30ZR18 98Y	SL	104370	10.5- <b>11.0</b> -11.5	31	25.5"	12.6	1653	51	816
335/30ZR18 102Y	SL	104340	11.5- <b>12.0</b> -12.5	33	25.9"	13.5	1874	51	801
235/35ZR19 91Y	XL	103840	8.0- <b>8.5</b> -9.5	25	25.5"	9.5	1356	50	816
245/35ZR19 89Y	SL	104440	8.0- <b>8.5</b> -9.5	25	25.8"	9.8	1279	51	806
265/30ZR19 89Y	SL	104240	9.0- <b>9.5</b> -10.0	26	25.3"	10.7	1279	51	821
265/35ZR19 94Y	SL	104490	9.0-9.5-10.5	29	26.3	10.7	1477	51	789
265/40ZR19 98Y	SL	104500	9.0-9.5-10.5	30	27.4	10.7	1653	51	759

275/35ZR19 100Y	SL	104420	9.0-9.5-11.0	30	26.6	10.9	1565	51	782
285/35ZR19 99Y	SL	104450	9.5- <b>10.0</b> -11.0	30	26.9"	11.4	1709	51	773
295/30ZR19 100Y	XL	104280	10.0- <b>10.5</b> -11.0	30	26.0"	11.8	1764	50	798
305/30ZR19 102Y	XL	104290	10.5- <b>11.0</b> -11.5	32	26.3"	12.3	1874	50	791
325/30ZR19 101Y	SL	104380	11.0- <b>11.5</b> -12.0	33	26.7"	13	1819	51	777
345/30ZR19 105Y	SL	104350	11.5- <b>12.0</b> -12.5	36	27.2"	13.8	1819	51	756
255/35ZR20 97Y	SL	104400	8.5-9.0-10.0	29	27	10.2	1433	51	769
285/30ZR20 99Y	SL	104150	9.5- <b>10.0</b> -10.5	31	26.8"	11.4	1709	50	776
285/35ZR20 100Y	SL	104150	9.5- <b>10.0</b> -11.0	33	27.9"	11.4	1764	51	745
305/35ZR20 104Y	SL	104410	10.0- <b>11.0</b> -12.0	35	28.4"	12.3	1984	51	731
315/30ZR20 101Y	SL	104300	10.5- <b>11.0</b> -11.5	35	27.5"	12.6	1819	51	756
325/30ZR20 102Y	SL	104390	11.0- <b>11.5</b> -12.0	35	27.7"	13	1874	51	750
Tire Size	Load ID	Product Code	Rim Width Range	Weight (lbs)	Overall Diameter	Overall Width	Max Load (lbs)	Max PSI	Revs Per Mile