



TOYO TIRES®

Buy Now



Toyo Proxes RR

Tire Size	Load ID	Product Code	Approved Rim Width Range	Weight	Tread Depth (1/32")	Overall Diameter (inch)	Overall Width (inch)	Max Load	Max PSI	UTQG	Revs Per Mile
205/60R13	SL	255150	5.5-6.0-7.5	19	3.6	22.7	8.2	1168	51	40 C A	916
205/50ZR15	SL	255000	5.5-6.5-7.5	20	3.6	23.0	8.5	1168	51	40 C A	902
225/45ZR15	SL	255140	7.0-7.5-8.5	21	3.6	23.0	8.9	1201	51	40 C A	905
225/50ZR15	SL	255080	6.0-7.0-8.0	22	3.6	23.9	9.2	1356	51	40 C A	869
245/40ZR15	SL	255240	8.0-8.5-9.5	21	3.6	22.7	9.8	1235	51	40 C A	914
225/50ZR16	SL	255160	6.0-7.0-8.0	24	3.6	24.9	9.2	1389	51	40 C A	858
245/45ZR16	SL	255130	7.5-8.0-9.0	23	3.6	24.6	9.5	1477	51	40 C A	843
225/45ZR17	SL	255270	7.0-7.5-8.5	22	3.6	25	8.9	1356	51	40 C A	832
235/40ZR17	SL	255120	8.0-8.5-9.5	22	3.6	24.4	9.5	1323	51	40 C A	851
245/40ZR17	SL	255260	8.0-8.5-9.5	23	3.6	24.7	9.8	1356	51	40 C A	840
255/40ZR17	SL	255110	8.5-9.0-10.0	24	3.6	25.0	10.2	1477	51	40 C A	830
275/40ZR17	SL	255100	9.0-9.5-11.0	28	3.6	25.7	10.9	1653	51	40 C A	809
255/35ZR18	SL	255300	8.5-9.0-10.0	24	3.6	25.0	10.2	1323	51	40 C A	831
P275/35ZR18	LL	255070	9.0-9.5-11.0	26	3.6	25.6	10.9	1201	44	40 C A	813
285/30ZR18	SL	255250	9.5-10.0-10.5	26	3.6	24.8	11.4	1433	51	40 C A	839
295/30ZR18	SL	255210	10.0-10.5-11.0	27.6	3.6	25.0	11.9	1477	51	40 C A	831
P305/35ZR18	LL	255170	10.0-11.0-12.0	30	3.6	26.4	12.3	1433	44	40 C A	786
315/30ZR18	SL	255180	10.5-11.0-11.5	29	3.6	25.5	12.6	1653	51	40 C A	816
345/35ZR18	SL	255290	11.5-12.0-13.5	35	3.6	27.5	13.8	2271	51	40 C A	755
235/35ZR19	SL	255230	8.0-8.5-9.5	23.1	3.6	25.5	9.5	1201	51	40 C A	816
295/30ZR19	SL	255220	10.-10.5-11.0	29.8	3.6	26.0	11.9	1565	51	40 C A	798
345/30ZR19	SL	255280	11.5-12.0-12.5	33	3.6	27.2	13.8	2039	51	40 C A	764
255/35ZR20	SL	255310	8.5-9.0-10.0	27	3.6	27.0	10.2	1433	51	40 C A	769
285/30ZR20	SL	255190	9.0-10.0-10.5	29	3.6	26.8	11.4	1521	51	40 C A	776
285/35ZR20	SL	255200	9.5-10.0-11.0	31.5	3.6	27.9	11.4	1764	51	40 C A	745
315/30ZR20	SL	255320	10.5-11.0-11.5	33	3.6	27.5	12.6	1819	51	40 C A	756
325/30ZR20	SL	255330	11.0-11.5-12.0	34	3.6	27.7	13	1874	51	40 C A	750

- Racing tread compound designed for increased grip and improved lap times
- Reinforced sidewall and High-Modulus bead filler provide excellent steering response and feedback
- Wear inspection holes strategically placed around the tire provide easy tread depth measurement
- Sidewall marking area designed with the racer in mind allows for easy labeling on the sidewall

Operating Temperature: 160°F to 220°F

Hot Inflation Pressures: High 30s to Low 40s (psi)

Camber: -2.5° to -5.0°

Caster: As much positive as possible

Suggested Applications - Race Prepared Vehicles - Road Racing, Endurance Racing